

HD100



Hotel/hospitality features



Customisable faceplate



Anti-bacterial housing



Power over Ethernet (PoE)



HD audio

The HD100 is designed as a comfortable, slimline modern hotel/guest room telephone that offers the most important features such as speed dialing to all hotel facilities and rooms, hands-free calling, and mute.

The PoE power supply and the Gigabit Ethernet connection allow the device to be integrated into a centrally managed, future-proof network infrastructure.

All settings of the HD100 can of course be administered centrally. The antibacterial housing protects against germs and is easy to clean. The large, visual LED call and message indicators as well as the individual labeling options complete the overall picture.

Basics and equipment

- Product information
 - Guest room phone | Corded handset | PN 00007000
 - Colour: gunmetal black
 - Anti-bacterial housing
- Equipment
 - Sturdy, solid construction
 - [Fully customisable faceplate for hotel branding and dialing instructions¹](#)
- Placement: indoor, desktop, nightstand, wall mounting

Dimensions and weight

- Dimensions (H × W × D, approx.)
 - Corded handset (on the base cradle, desk mounted): 79 mm × 176 mm × 163 mm
 - Corded handset (on the base cradle, wall mounted): 79 mm × 78 mm × 211 mm
- Weight (approx.)
 - Corded handset (on the base cradle): 665 g

Indicators and keys

- 2 LED indicators
 - Corded handset
 - Mute status indication: 1 red LED
 - Telephone base
 - Call status indication | Message waiting indication (MWI): 1 red LED
- 26 hard keys in total
 - Corded handset
 - 12 keys (standard ITU telephone keypad)
 - 3 dedicated audio keys
 - *MUTE* → Mute (with red LED)
 - *VOL+* → Volume +
 - *VOL-* → Volume -
 - 2 dedicated function keys
 - *EMERGENCY* → Emergency
 - *MESSAGES* → Message

- 2 programmable function keys: Speed dialling
- Telephone base
 - 3 dedicated audio keys
 - *VOL+* → Volume +
 - *VOL-* → Volume -
 - *SPEAKER* → Speakerphone (with red LED)
 - 4 programmable function keys: Speed dialling

Audio devices and features

- Telephone base
 - Casing microphone
 - Casing speaker
- Corded handset
 - Microphone
 - Handset earpiece
 - Hearing aid compatible (HAC)
- Built-in assignable ringtones

Interfaces and connections

- Power options
 - [Power over Ethernet \(PoE\)](#)
 - IEEE 802.3af, class 2
 - Power adapter¹
 - 100 - 240 V AC / 50/60 Hz / 500 mA | 5 V DC / 2 A
- Wired interfaces
 - Telephone base
 - Network connectivity: RJ45-8P8C socket → Gigabit Ethernet (GbE)
 - Power adapter:¹ coaxial power connector (socket)
 - Handset cord: custom socket
 - Corded handset
 - Handset cord: custom socket

Administration interfaces and setup

- Configuration and setup via voice menu
- [Configuration and setup via menu-driven web user interface \(WUI\)](#)
- Advanced SIP configuration tool for easy mass deployment and phone monitoring
- [Secure Redirection And Provisioning Service \(SRAPS\)](#) support

Networking technologies and protocols

- VLAN support
- [SIP \(RFC 3261\)](#)

Interoperability

- Interoperable with all major IP-PBX platforms

Call features

- 1 SIP identity / account
- Speed dialling via function keys
- Speakerphone mode (via dedicated function key)
- Mute microphone (via dedicated function key)
- [Multicast paging](#)

Environmental conditions

- Operating ambient temperature: 5 °C - +45 °C
- Humidity (non-condensing): 5 % - 95 %

Package contents

- Hardware
 - Telephone base
 - Corded handset
 - Footstand
 - Wall mount kit
 - 2 Ethernet cables: Cable length (approx.) 140 mm | 2 m
- Documentation
 - [Quick Installation Guide](#)

Snom accessories and compatible devices

- Power adapter:¹ Telephone base PSU
 - EU: PN 00004687
 - UK: PN 00004688
 - AU: PN 00004689

¹ Available separately

Series overview



HM201



HD100



HD101



HD1



HD300



HD350W



HD351W



HD3

Disclaimer

Further information: [Snom HD100 webpage](#) | [Snom Service Hub](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.