

HD3



Hotel/hospitality features



DECT handset



HD audio



Anti-bacterial housing

Basics and equipment

- Product information
 - Cordless DECT handset | Charging cradle | PN 00007011
 - Colour: gunmetal black
 - Sturdy, solid construction
 - Customisable section for colour or hotel branding
 - Anti-bacterial housing
- Placement: indoor, desktop, nightstand

Dimensions and weight

- Dimensions (H x W x D, approx.)
 - Handset: 48 mm x 21 mm x 203 mm
 - Charging cradle: 51 mm x 121 mm x 133 mm
 - Handset (on the charging cradle, desk mounted): 53 mm x 56 mm x 216 mm
- Weight (approx.)
 - Handset: 145 g
 - Charging cradle: 72 g
 - Handset (on the charging cradle, desk mounted): 344 g

Indicators and keys

- Handset: 5 LED indicators
 - Message waiting indication (MWI): 1 red LED
 - Flash/Talk key indication: 1 green LED
 - Speakerphone mode: 1 red LED
 - Mute status indication: 1 red LED
 - Low battery indication: 1 red LED
- Charging cradle: 1 LED indicator
 - Charging indication: 1 red LED
- Handset: 23 hard keys in total
 - 12 keys (standard ITU telephone keypad), backlit
 - 4 dedicated audio keys: Mute (with red LED), Speakerphone (with red LED), Volume +, Volume -
 - 3 programmable function keys: Speed dialling

- 4 dedicated function keys:
 - Offhook (with green LED)
 - Onhook
 - Message
 - Hold

Audio devices and features

- Microphone
- Handset earpiece: Hearing aid compatible (HAC)
- Casing speaker: Speakerphone mode (via dedicated function key)
- Built-in assignable ringtones

Interfaces and connections

- Power options
 - Handset: Battery lithium-ion, 3.7 V, 1,000 mAh, removable, rechargeable, up to 7 h talk time, up to 120 h standby time, up to 11 h charging time
 - Charging cradle: Power adapter (VT-PLII) 100 - 240 V AC, 50/60 Hz, 150 mA | 6 V DC, 450 mA, 2.7 W
- Wired interfaces
 - Charging cradle: coaxial power connector (socket)
- Wireless interfaces
 - DECT

DECT technology and features

- Standard: DECT
 - Wideband audio
- Frequency band
 - EU & UK & AU: 1,881.792 - 1,897.344 MHz
- Easy registration to compatible base stations

Call features

- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Hold (via dedicated function key)
- Quick call answer (by simple pick-up from the base/charger)
- [Multicast paging](#)

Environmental conditions

- Operating ambient temperature:
 - 5 °C - 45 °C
- Humidity (non-condensing):
 - 5 % - 95 %

Package contents

- Hardware
 - DECT handset **HD3**
 - Battery
 - Charging cradle
 - Power adapter
- Documentation
 - [Quick Installation Guide](#)

Snom accessories and compatible devices

- Guest room phone: [HD351W \(PN 00007009\)](#)
- Battery HD3 (PN 00004627)
- Power adapter: HD3 PSU
 - EU: PN 00004683
 - UK: PN 00004684
 - AU: PN 00004685

Series overview



HM201



HD100



HD101



HD1



HD350W



HD351W



HD3

Disclaimer

Further information: [Snom website](#) | [Snom Service Hub](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.